



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE2570 (NPN) & NTE2571 (PNP) Silicon Complementary Transistors High Current Switch TO-220 Full Pack

Features:

- Low Collector–Emitter Saturation Voltage
- High Current Capacity

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Collector–Base Voltage, V_{CBO}	90V
Collector–Emitter Voltage, V_{CEO}	80V
Emitter–Base Voltage, V_{EBO}	6V
Collector Current, I_C	
Continuous	7A
Peak	12A
Collector Power Dissipation, P_C	
$T_A = +25^\circ\text{C}$	2W
$T_C = +25^\circ\text{C}$	30W
Operating Junction Temperature, T_J	$+150^\circ\text{C}$
Storage Temperature Range, T_{stg}	-55° to $+150^\circ\text{C}$

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector Cut–Off Current	I_{CBO}	$V_{CB} = 80\text{V}, I_E = 0$	–	–	0.1	mA
Emitter Cut–Off Current	I_{EBO}	$V_{EB} = 4\text{V}, I_C = 0$	–	–	3.0	mA
DC Current Gain	h_{FE}	$V_{CE} = 2\text{V}, I_C = 1\text{A}$	100	–	280	
		$V_{CE} = 2\text{V}, I_C = 4\text{A}$	30	–	–	
Gain–Bandwidth Product	f_T	$V_{CE} = 5\text{V}, I_C = 1\text{A}$	–	20	–	MHz
Collector–Emitter Saturation Voltage NTE2570	$V_{CE(sat)}$	$I_C = 5\text{A}, I_B = 10\text{mA}$	–	–	0.4	V
			–	–	0.5	V
Collector–Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = 1\text{mA}, I_E = 0$	90	–	–	V
Collector–Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 1\text{mA}, R_{BE} = \infty$	80	–	–	V
Emitter–Base Breakdown Voltage	$V_{(BR)EBO}$	$I_C = 1\text{mA}, I_C = 0$	6	–	–	V

Electrical Characteristics (Cont'd): ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Turn-On Time NTE2570	t_{on}	$V_{CC} = 50\text{V}, V_{BE} = -5\text{V},$ $10I_{B1} = -10I_{B2} = I_C = 2\text{A},$ Pulse Width = $20\mu\text{s}$ Duty Cycle $\leq 1\%$	-	0.1	-	μs
NTE2571			-	0.2	-	μs
Storage Time NTE2570	t_{stg}		-	1.6	-	μs
NTE2571			-	0.7	-	μs
Fall Time NTE2570	t_f		-	0.4	-	μs
NTE2571			-	0.2	-	μs

Note 1. For NTE2571, the polarity is reversed.

